

EBARA MODEL: CNP Ax NFPA20 UL/FM HSC FIRE PUMPS

CNP Ax SINGLE/MULTI STAGE
50/60 HZ 2/4 POLES & OTHERS SPEED



RANGE OF RATED CERTIFIED PARAMETER FOR SINGLE-STAGE HSC FIRE PUMP

FLOW CAPACITY(usgpm):						
300	400	450	500	750	1000	1250
1500	2000	2500	3000	3500	4000	4500
5000	5500	6000	6500	7000	7500	8000
PRESSURE HEAD(psi): 40 to 367						

DRIVER SPEED(rpm):
50Hz, 2/4 Pole Speed Electric Motor: 3000/1500 Diesel Engine: 3000
60Hz, 2/4 Pole Speed Electric Motor: 3600/1800 Diesel Engine: 1800
Other Speed Diesel Engine: 2000/2100/2350/2600

RANGE OF RATED CERTIFIED PARAMETER FOR MULTI-STAGE HSC FIRE PUMP

FLOW CAPACITY(usgpm):				
500	750	1000	1250	1500
PRESSURE HEAD(psi): 236 to 616				

DRIVER SPEED(rpm):
50Hz, 2 Pole Speed Electric Motor: 3000 Diesel Engine: 3000
60Hz, 2/4 Pole Speed Electric Motor: 3600/1800 Diesel Engine: 1800

